

ARTCOOL MIRROR

ARNU05GSJR4 / ARNU07GSJR4 / ARNU09GSJR4
ARNU12GSJR4 / ARNU15GSJR4

ARNU18GSKR4 / ARNU24GSKR4



Model	Independent Unit			ARNU05GSJR4	ARNU07GSJR4	ARNU09GSJR4	ARNU12GSJR4	ARNU15GSJR4
Capacity	Cooling	Nom	kW	1.6	2.2	2.8	3.6	4.5
	Heating	Nom	kW	1.8	2.5	3.2	4.0	5.0
Power Input	Cooling / Heating	Nom ¹⁾	W	12	13	15	19	21
	Cooling / Heating	Rated ²⁾	W	21	21	21	21	21
Power Supply	Ø / V / Hz			1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60
Airflow Rate	Cooling	H / M / L	m ³ /min	6.5 / 6.0 / 5.5	7.0 / 6.5 / 5.5	8.2 / 7.0 / 5.5	9.5 / 8.2 / 6.5	10.5 / 9.0 / 7.0
	Heating	H / M / L	m ³ /min	6.5 / 6.0 / 5.5	7.0 / 6.5 / 5.5	8.2 / 7.0 / 5.5	9.5 / 8.2 / 6.5	10.5 / 9.0 / 7.0
Sound Pressure	H / M / L		dBA	30 / 29 / 28	32 / 30 / 28	34 / 32 / 28	37 / 34 / 30	42 / 39 / 32
Sound Power	H / M / L		dBA	54 / 53 / 52	54 / 53 / 52	55 / 54 / 52	55 / 54 / 53	58 / 56 / 54
Dimensions	Body	W x H x D		mm	895 x 285 x 205	895 x 285 x 205	895 x 285 x 205	895 x 285 x 205
Net Weight				kg	10.8	10.8	10.8	10.8
Piping Connection	Liquid			mm	6.35	6.35	6.35	6.35
	Gas			mm	12.7	12.7	12.7	12.7
	Drain	I.D		mm	16.0	16.0	16.0	16.0

* This product contains Fluorinated Greenhouse Gases. (R410A)

1) Nom. : Performance tested under EN14511

2) Rated : Max power input allowed for fan motor

Note : 1. Capacities are based on the following conditions

- Cooling : Indoor temp. 27°C (80.6°F) DB / 19°C (66.2°F) WB, Outdoor temp. 35°C (95°F) DB / 24°C (75.2°F) WB, Interconnecting piping length 7.5m, Level difference of zero

- Heating : Indoor temp. 20°C (68°F) DB / 15°C (59°F) WB, Outdoor temp. 7°C (44.6°F) DB / 6°C (42.8°F) WB, Interconnecting piping length 7.5m, Level difference of zero

2. Due to our policy of innovation some specifications may be changed without notification

3. I.D : ' Internal Diameter '

Model	Independent Unit			ARNU18GSKR4	ARNU24GSKR4
Capacity	Cooling	Nom	kW	5.6	7.1
	Heating	Nom	kW	6.3	8.0
Power Input	Cooling / Heating	Nom ¹⁾	W	27	39
	Cooling / Heating	Rated ²⁾	W	40	40
Power Supply	Ø / V / Hz			1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60
Airflow Rate	Cooling	H / M / L	m ³ /min	12.5 / 12.0 / 11.3	14.0 / 12.7 / 11.5
	Heating	H / M / L	m ³ /min	12.5 / 12.0 / 11.3	14.0 / 12.7 / 11.5
Sound Pressure	H / M / L		dBA	38 / 35 / 33	43 / 39 / 35
Sound Power	H / M / L		dBA	57 / 54 / 52	62 / 58 / 54
Dimensions	Body	W x H x D		mm	1,030 x 325 x 245
Net Weight				kg	15.4
Piping Connection	Liquid			mm	6.35
	Gas			mm	12.7
	Drain	I.D		mm	16.0

* This product contains Fluorinated Greenhouse Gases. (R410A)

1) Nom. : Performance tested under EN14511

2) Rated : Max power input allowed for fan motor

Note : 1. Capacities are based on the following conditions

- Cooling : Indoor temp. 27°C (80.6°F) DB / 19°C (66.2°F) WB, Outdoor temp. 35°C (95°F) DB / 24°C (75.2°F) WB, Interconnecting piping length 7.5m, Level difference of zero

- Heating : Indoor temp. 20°C (68°F) DB / 15°C (59°F) WB, Outdoor temp. 7°C (44.6°F) DB / 6°C (42.8°F) WB, Interconnecting piping length 7.5m, Level difference of zero

2. Due to our policy of innovation some specifications may be changed without notification

3. I.D : ' Internal Diameter '

Accessories

Model	ARNU05GSJR4	ARNU07GSJR4	ARNU09GSJR4	ARNU12GSJR4	ARNU15GSJR4
Dry Contact	Simple (1 Contact Point with Case)		PDRYCB000		
	2 Contact Point		PDRYCB400		
	For Thermostat (On-Off / Mode / Fan Speed)		PDRYCB300		
	Modbus Communication		PDRYCB500		
EEV Kit for MULTI V Indoor					PRGK024A0

Wired Remote Controller							Wireless Remote Controller
Premium	Standard III		Standard II		Simple	Simple for Hotel	
PREMTA000 PREMTA000A PREMTA000B	PREMTB100 (White)	PREMTBB10 (Black)	PREMTB001 (White)	PREMTBB01 (Black)	PQRCVCLQ (Black) PQRCVCLQW (White)	PQRCHCA0Q (Black) PQRCHCA0QW (White)	PQWRHQ0FDB

Accessories

Model	ARNU18GSKR4	ARNU24GSKR4	
Dry Contact	Simple (1 Contact Point with Case)		PDRYCB000
	2 Contact Point		PDRYCB400
	For Thermostat (On-Off / Mode / Fan Speed)		PDRYCB300
	Modbus Communication		PDRYCB500
EEV Kit for MULTI V Indoor			PRGK024A0

Wired Remote Controller							Wireless Remote Controller
Premium	Standard III		Standard II		Simple	Simple for Hotel	
PREMTA000 PREMTA000A PREMTA000B	PREMTB100 (White)	PREMTBB10 (Black)	PREMTB001 (White)	PREMTBB01 (Black)	PQRCVCLQ (Black) PQRCVCLQW (White)	PQRCHCA0Q (Black) PQRCHCA0QW (White)	PQWRHQ0FDB